

Dimensions

STANDARD

Height: 7.5" Width: 12.3" Depth: 2.0"

NEW YORK CITY APPROVED

Height: 11.0" Width: 14.5" Depth: 2.3"

Options Add Suffix to Catalog

Number

-6 (2) 6VDC Lamps for AC/6VDC Remote Operation

-12 (2) 12VDC Lamps for AC/12VDC Remote Operation

-DMP Damp Location Listing (Damp

-DS Double LED Strips for Increased Illumination or 2 Independent AC Circuit Operation

-HI High-Intensity LEDs

-NY New York City Approved with 8" Letters

-REC Recessed Housing (Single-Face Only)

-TP Tamper-Proof Screws

-U Universal Face (Additional Backplate – Double-Face Signs Only)

Accessories

Order Separately

Wire Guard (for Single-Face Back Mount Only)

P12W 12" Pendant Kit, White*

P12B 12" Pendant Kit, Black*

*Pendant Kits from 12" to 84" Available

Vandal-Deterrent Shield (for Single-Face Back Mount Only)







Series Features

• 120/277 VAC Operation



• Maximum Input Rating (120 or 277VAC)

Standard 1.7 Watts DS Option 3.5 Watts



• Illuminates with Uniform Color and Brightness

• Indirect Placement for Diffused Legend Output


• Ceiling, End or Back Mount


Canopy





• Directional Chevron Snapouts






- Easy Installation
- UL Listed


Additional Emergency Unit Features



Integrated Solid State System









• Increased LED Brightness Level in Emergency Mode

• Sealed Nickel Cadmium Battery



- 5-Year Shelf Life
- 10-Year Battery Warranty
- Maintenance-Free



- 3+ Hours Illumination in Emergency Mode*
- Test Switch
- LED (Power On) Indicator

Ordering Information

EXFL	1	R	W	W	-DS
AL-75752-AC Only EXFL – Emer.	# Faces 1 2	Letter Color Red Green	Stencil Color <u>W</u> hite <u>B</u> lack <u>PM</u> Painted Matte Chrome	Housing Color <u>W</u> hite* <u>B</u> lack <u>PM</u> Painted Matte Chrome	Option Factory Options



^{*}Longer Illumination Times Available. Consult Factory.