

FOR USE IN TRAUMA AND X-RAY ENVIRONMENTS. EQUIPPED WITH A FIBRE RESIN FILM SURFACE AND HIGH DENSITY RADIOLUCENT MATTRESS. A TOTAL-VIEW DESIGN, WITH FULL SURFACE ACCESSIBILITY FOR CASSETTE PLACEMENT



## MOVEMENT

HEIGHT ADJUSTMENT: 22" TO 35<sup>1/2</sup>" HANDS-FREE TRENDELENBERG: +18° TO -18° PNEUMATIC ASSIST FOWLER: 0° TO 90° DROP-RAIL, COLLAPSIBLE SIDE-RAILS 8" ALL-SURFACE, LOCKING CASTERS ACCU-STEER 5TH WHEEL POSI-LOCK BRAKING SYSTEM

## DIMENSIONS

TOTAL DIMENSIONS: 81" X 32<sup>1/2</sup>" LITTER DIMENSIONS: 81" X 28<sup>1/2</sup>" MATTRESS DIMENSIONS: 75" X 29" X 3" DROP-RAIL SIDE-RAILS: 60<sup>1/2</sup>" X 12<sup>1/2</sup>"



STANDARD: HIGH DENSITY FOAM MATTRESS WITH CONDUCTIVE COVER OPTIONAL: VISCOLASTIC, PRESSURE SENSITIVE MATTRESS, WITH FOUR-WAY, ELASTATEX STRETCH COVER

info@alcosales.com

## 800.323.4282 www.alcosales.com

