

SNMP/Web Interface Card, Remote Cooling Management

AL-83987





Highlights

- Enables remote management of Tripp Lite air conditioning unit
- Controls temperature, fan speed and dehumidification modes
- Sends alerts in case of power failure, high temperature, etc.
- Installs easily in unit's accessory slot
- Includes ENVIROSENSE temperature and humidity sensor

Package Includes

- SNMP/Web Interface Card
- ENVIROSENSE module
- Configuration cable(73-1025)
- MAC address label(located on AL-83987)
- Owner's Manuals

Description

The AL-83987 SNMP/Web Interface Card adds remote monitoring and management capabilities to select air conditioning units, including the AL-83985. By installing the AL-83987 into the unit's

accessory slot, you will be able to control the cooling unit over the Ethernet network from any location via SNMP, SSH, telnet or web browser. Monitor temperatures, adjust fan speed, and activate dehumidification modes. You can also review logs remotely and receive alerts. LEDs confirm network connection, speed and card initialization. The included ENVIROSENSE® module connects to the AL-83987's PS/2 port to monitor temperatures and humidity up to 12 feet away from the primary unit, allowing its operation to be based on the intake air temperature where the sensor is mounted. The ENVIROSENSE also lets you monitor smoke detectors, fire alarms and security systems through a dry-contact interface.

Features

Control Your Cooling Unit from Anywhere

- Turn select in-rack(such as Tripp Lite AL-83985) and portable air conditioning units into a managed network device
- Access unit via SNMP, SSH, telnet or web browser
- Monitor temperatures
- Adjust fan speed
- Activate dehumidification modes
- Review logs
- Receive alerts
- . LEDs confirm network connection/speed and card initialization

Includes ENVIROSENSE Temperature/Humidity Sensor Module

- Monitors temperature and humidity up to 12 ft. away
- Controls smoke detectors, fire alarms and security systems via dry-contact interface
- Connects easily to AL-83987's PS/2 port

Easy to Set Up and Manage

- Installs easily into cooling unit's front SNMP accessory slot
- . Included PowerAlert® software interface provides single display for controlling cooling units and ENVIROSENSE modules
- Compliant with the Federal Trade Agreements Act(TAA) for GSA Schedule purchases

Specifications

OVERVIEW	
Accessories Type	SNMP Card Module
INPUT	
Nominal Input Voltage Description	12V DC
USER INTERFACE, ALERTS & CONTROLS	
LED Indicators	1 Link LED to confirm connection and indicate speed and 1 Status LED to indicate when the card is initialized
PHYSICAL	
Shipping Dimensions (hwd / in.)	2.28 x 6.5 x 6.93
Shipping Dimensions (hwd / cm)	5.8 x 16.5 x 17.6
Shipping Weight (lbs.)	0.40
Shipping Weight (kg)	0.18
WARRANTY	
Product Warranty Period (Worldwide)	2-year limited warranty



Follow us on Twitter at: www.twitter.com/ALCOSales

Like us on Facebook at: www.facebook.com/ALCOSalesServiceCo info@alcosales.com www.alcosales.com